

TAYLOR SHUTTER COLLECTION

DESIGNED FOR EASY CARE AND CLEANING



CUSTOMER SERVICE

208 Main Road, Walmer, Port Elizabeth | +27 (0) 41 180 4000 | office@duoproducts.co.za

www.duoproducts.co.za





HOW TO OPERATE YOUR THERMOWOOD® SHUTTERS



Use the tilt rod (if fitted) to open and close the louvres, alternatively open and close the louvres with your hand.



If you have a bi-fold configuration, fold the shutters from side closest to wall and gather stacking this way, with the louvres in a closed position. Never attempt to force the bi-fold action.



In order to correctly close the louvres, stroke the palm of your hand from bottom to top over louvres until closed.



Frequently clear obstructions and dirt from the bottom track using a vacuum cleaner, to make sure the track remains clean, allowing the shutters to move along them smoothly.

**THERMOWOOD®
SHUTTERS**

HOW TO CLEAN

HOW TO CLEAN YOUR THERMOWOOD® SHUTTERS



Dust frequently with a soft cloth or brush.



Water can be used to clean the shutters.



Do not use any chemical solutions on this product.



Our Thermowood® Shutters carry a warranty up to 3 years from date of purchase against faulty workmanship or components as well as faulty installations. Terms and conditions apply.





HOW TO OPERATE YOUR

SHUTTERGUARD® & HURRICANE ALUMINIUM SHUTTERS



Louvers are opened by tilting to your desired position using your hands.




If you have a bi-fold configuration, fold the shutters from side closest to wall and gather stacking shutters this way, with the louvers in a closed position. Never attempt to force the bi-fold action.




A hinge handle is supplied for reverse hinged shutters for ease of opening.



Remove the keys when bi folding – as keys may break off when panels are being stacked (the louvers should not touch the key).




To lock (interior lock): turn the knob clockwise until both bolts are fully extended into the top & bottom track and you hear the knob click to lock. **To lock (exterior lock):** turn the knob anti-clockwise until both bolts are fully extended into the top & bottom track and you hear the knob click to lock.



SHUTTERGUARD® ONLY:

To unlock (interior lock): use your unique security key & turn anti-clockwise until you hear it unlock, then turn the knob anti-clockwise to retract the bolts. **To unlock (exterior lock):** use your unique security key & turn clockwise until you hear it unlock. Then turn the knob clockwise to retract the bolts.



Lock & unlock your louvers by pressing the small button up or down. Louvre lock is an optional extra on Hurricane shutters.

HOW TO CLEAN

YOUR SHUTTERGUARD® & HURRICANE SHUTTERS



Tension of louvres may be adjusted by turning small screws at the back of tilt rods to your desired tension.



Frequently clean bottom track from obstructions and dirt, using a vacuum cleaner.



Dust frequently and wipe with a mild solution of dishwashing liquid.



Outside shutters may be sprayed down with clean water.



Removable stickers are placed on the ShutterGuard® and Hurricane turning knobs for your ease of use. Please feel free to remove these once you are comfortable with the operating system.

Our Shutterguard® and Hurricane Aluminium Shutters carry a warranty up to 10 years from date of purchase against faulty workmanship or components as well as faulty installations. Terms and conditions apply.



QUALITY. INNOVATION. TRUST.



Duo Shutters are a preferred Taylor distributor in Port Elizabeth

OFFICES & SHOWROOMS

208 Main Road, Walmer, Port Elizabeth | +27 (0) 41 180 4000 | office@duoproducts.co.za

www.duoproducts.co.za

