4 • 000 I I R SHU FFR

OFFICES & SHOWROOMS 208 Main Road, Walmer, Port Elizabeth | +27 (0) 41 180 4000 | office@duoproducts.co.za

www.duoproducts.co.za

E H

Natural light. Privacy on demand.



RUST PROOF



-CONTROL LIGHT, NOISE & TEMPERATURE





Thermowood® Shutters are practical and elegant, custom-made, louvre door shutters, manufactured from a durable, specially engineered wood substitute – extruded PVC – that has been thoroughly tested under stringent humid, hot and dry conditions to ensure longevity.

Whether you want to invite light and a sense of space into your home at the ocean's edge or in the in the middle of the Karoo, or whether you are looking for a room divider or alternative cupboard door in a room influenced by moisture, Thermowood® Shutters will deliver on its' promise of merging indoor and outdoor living - elegantly.

TECHNICAL SPECIFICATIONS

UV Blockage:	100% when closed
Weight:	8 kg/m2
Min/Max Width:	240 - 600mm
Min/Max Height:	450 - 2900mm
Material:	Extruded PVC

TECHNICAL FEATURES

\oslash	3 Year Warranty
->	Control of light, noise and temperature
\Diamond	Impervious to moisture
\otimes	Will not crack, split or warp
\bigcirc	Rust Proof
7	Easy to clean

TRACK OPTIONS

either the extrem left or extreme right shutter is fixed and does not move The other shutters therefore pivot from this fixed poin

LIP track which has a 'lip' coming up and over and lies against the top frame opening, to neaten			
it off.	l		L


NO LIP E		
NULIFL		Г
The top track		l
fits in flush		l
with the		l
opening and		l
doesn't come		l
up and over		l
the top wall		l
opening.		L

Top track with lip (To neaten uneven walls, window frames, gaps etc)



PIVOT OPTIONS





Bi fold

Pivot, either left or right

Standard Frame





Side profile of Thermowood® louvre

AVAILABLE STANDARD COLOURS

olland	Lime Wash	Magnolia
atin White	Ash Grey	Alu White


CUSTOM COLOURS

Kindly note no custom colours are available for Thermowood®



Face fixed with top track (stands proud against the opening

TILT ROD



Reveal fixed with top track (set inside the window/door reveal)

Tilt rods offer owners the opportunity to open and close the shutters with the rod which is placed on the louvres, running down the middle of each shutter panel



	7

Decorative Fram

With tilt rod

Without tilt rod (also known as clear view)

HOW OUR RANGE **OF SHUTTERS STACK UP**







			A A MATTER AND
	ShutterGuard® Aluminium Security Shutters	Hurricane Aluminium Shutters	Thermowood® Shutters
Material	Aluminium	Aluminium	Extruded PVC (specially engineered wood substitute)
Internal use	~	~	✓
External use	\checkmark	~	×
Rustproof	~	~	 ✓
Deliver on security	~	 Only if you add Louvre Locks as an optional extra** 	×
Stackable	~	~	 ✓
Suitable for doors & windows	~	~	✓
Warranty	10 years	10 years	3 years
Colours *see below for custom colour timings and surcharge	Matte White, Matte Bronze, Matte Light Grey, Matte Stone Grey, Matte Anthracite Grey	Matte White, Matte Bronze, Matte Light Grey, Matte Stone Grey, Matte Anthracite Grey	Satin White, Magnolia, Lime Wash, Alu-White, Holland or Ash. No custom colours available.
Manufacture time Excluding delivery which requires 5 - 7 working days from our Cape Town factory.	2 weeks: Matte White, Matte Bronze 3 weeks: Matte Light Grey, Matte Stone Grey, Matte Anthracite Grey Custom colours available*	2 weeks: Matte White, Matte Bronze 3 weeks: Matte Light Grey, Matte Stone Grey, Matte Anthracite Grey Custom colours available*	2 weeks: All standard colours
Configurations	Bi-Fold, Bi-Pass, Slider, Cottage Style or Cottage Arch Frame configuration	Bi-Fold, Bi-Pass, Slider, Cottage Style or Cottage Arch Frame configuration	Bi-Fold, Bi-Pass, Cottage Style Frame, Cottage Arch Frame, Standard Frame or Decorative Frame. Available with centre located tilt rod or Clearview [®] options.
Sizes	Min-Max shutter width: 250-850mm Min-Max shutter height: 650-2900mm	Min-Max shutter width: 250-850mm Min-Max shutter height: 500-2900mm	Min-Max shutter width: 240-600mm Min-Max shutter height: 450-2900mm
Mechanism / Components	Supplied with hinges, brackets and tracks for smooth operation	Supplied with hinges, brackets and tracks for smooth operation	Supplied with Clearview [®] (no tiltrod) or Tiltrod (middle of the louvres running vertical) and tracks for smooth operation
Accessories	Louvre Locks	Louvre Locks only as an optional extra*;	ć
Light Control	Yes. New Astragal frame removes light gap between shutter panels.	New Astragal frame removes light gap between shutter panels. This is only applied as an optional extra **	Yes. Light control depends on the louvres tilt when closing/opening.
Privacy Control	85 - 100% (not possible to see through closed shutters)	85 - 100% (not possible to see through closed shutters)	85 - 100% (not possible to see through closed shutters)
Security	ShutterGuard [®] is a security shutter system. Patented Taylor 2-way aluminium Gear-Lock System. 6cm patented bolt secures shutters to the floor. 3.4cm bolt secures shutters to the top track.	Hurricane Shutters can only be considered a security shutter if a louvre lock is added. Should you wish to add lourvre locks you are able to, to secure your louvres shut.**	Thermowood $^{\textcircled{R}}$ is not a security shutter system.
		*Custom colours are available at a	surcharge and will add an extra 1 week to the lead time

*Custom colours are available at a surcharge and will add an extra 1 week to the lead time **Optional extras for Hurricane Shutters include: Astragal Frame to remove light gap between shutter panels and louvre locks to lock louvres.